

Tuckunder range

Tuckunders with lifting capacities up to 1500kgs



Why a DEL tail lift?



■ Made to order

From our 64,000ft factory in Witney, we have the expertise and experience to manufacture a wide range of tail lifts. Every tail lift we produce is tailor made to meet your exact requirements.

■ Quality assured

As a ISO 9001:2008 certified organisation, we continuously measure our performance and constantly work to improve upon it. We are committed to supply high quality products and services.

■ Durability

With DEL products, not only will you get a great product to suit your requirements but also one that will last. Each lift has been thoroughly tested to ensure you have many years of trouble free operation.

■ Top finish

Steel components are plated or galvanised to offer maximum protection against corrosion. This will help enhance your company's image plus increasing the vehicle residual value.

■ Comprehensive warranty

Each product comes with a comprehensive 12 months parts and labour warranty package as standard. This provides you with 24 hours a day, 365 days a year breakdown cover to ensure that you will never be left stranded. Extended warranty packages are available if required.

■ After care

We expect that you will have many years of trouble free use from our products. It is comforting to know however that in the rare event of a problem occurring during operation that our friendly, helpful and experienced staff are only a phone call away.

DA1000 For 5 tonne vehicles & above



■ This is the only 1000kg tuckunder lift with a galvanised steel frame and an all aluminium platform, in existence. It features greaseless heavy-duty bearings to reduce maintenance costs. The lift also comes with a three year warranty against corrosion as standard.

Features

- Fully galvanised steelwork for added protection against corrosion.
- Low installed weight to maximise vehicle payload.
- Lifting ram fully closed when lift in stowed position to prevent ram piston from 'pitting' and reduce risk of leaking.
- Wanderlead control included for greater operator flexibility.



Ideal for

- Parcel deliveries
- Home delivery services
- Haulage companies
- Multi-purpose vehicles

Technical specification for standard build

Model	Lifting capacity	Platform material	Platform depth	Ramp size	Platform width	Floor height		Voltage	
						min	max		
DA1000LG	1000kg	Aluminium	1085mm	150mm	1980mm	975mm	1190mm	12v or 24v	340kg
DA1000HG	1000kg	Aluminium	1170mm	205mm	2135mm	1120mm	1400mm	24v	420kg

DA1500 For 12 tonne vehicles & above



■ This is the only 1500kg tuckunder lift with a galvanised steel frame and an all aluminium platform, in existence. It features greaseless heavy-duty bearings to reduce maintenance costs. The lift also comes with a three year warranty against corrosion as standard.

Features

- Fully galvanised steelwork for added protection against corrosion.
- Twin ram system to offer greater stability during tail lift operation.
- Lifting ram fully closed when lift in stowed position to prevent ram piston from 'pitting' and reduce risk of leaking.
- Wanderlead control included for greater operator flexibility.



Ideal for

- Parcel deliveries
- Home delivery services
- Haulage companies
- Multi-purpose vehicles

Technical specification for standard build

Model	Lifting capacity	Platform material	Platform depth	Ramp size	Platform width	Floor height min	Floor height max	Voltage	Weight
DA1500HDG	1500kg	Aluminium	1170mm	205mm	2135mm	1120mm	1400mm	24v	455kg

DA500SM for 7.5 Tonne & above vehicles



■ This lightweight tuckunder is unique as it is side mounted and requires limited body modifications for installation. When the lift is not in use, it sits discreetly behind the side impact bars.



Features

- Stow light indicator included in cab to show vehicle operator the lift has been stowed away correctly.
- Low installed weight to maximise vehicle payload.
- Lifting ram fully closed when lift in stowed position to prevent ram piston from 'pitting' and reduce risk of leaking.
- Wanderlead control included for greater operator flexibility.

Ideal for

- Paper shredding
- Household collections
- Highways
- Builders merchants

Technical specification for standard build

Model	Lifting capacity	Platform material	Platform depth	Ramp size	Platform width	Floor height min	Floor height max	Voltage	Weight
DA500SML	500kg	Aluminium	1015mm	205mm	1200mm	975mm	1190mm	12v or 24v	240kg
DA500SMH	500kg	Aluminium	1015mm	205mm	1200mm	1120mm	1400mm	24v	265kg

Tail lift options

As every DEL tail lift is made to order, it allows you to tailor the lift to meet your exact requirements. Listed below are a selection of our most popular options available for the tuckunder range. If you cannot find what you are looking for or have something specific in mind, give us a call and we will be more than happy to help provide you with a solution.



Detachable side guards

The lightweight guards are stored within the vehicle bodywork. When required, the tail lift operator 'drops' the guards into sockets already fitted to the platform.



Trolley stops

The spring activated trolley stops are recommended as an alternative to hinged ramps, if wheeled trolleys are loaded/unloaded. The stop is "inactive" until the lever is slid back by foot. When released, the trolley stop springs open automatically, preventing wheeled trolleys from rolling off the platform.



Lockable control box

This control box provides our wanderlead control with an ideal weatherproof storage facility and as it is lockable, it prevents unauthorised operations. Each box is supplied with a set of keys.



Flashing lights

Installed to the rear of the platform on both sides and automatically illuminates when platform is open to maximise awareness.



Battery guard system

To prevent continuous tail lift use draining the vehicle battery, this unit will provide a signal (or cut of the power supply) before voltage drops too low. The operator may then start the vehicle to recharge the battery and press the reset button to activate the battery guard unit. It comes fully pre-wired in our tail lift.

DEL IS A CARGOTEC BRAND



DEL

DEL Equipment (UK) Ltd.
Building 1
Windrush Industrial Park,
Witney, Oxon, OX29 7HA
Tel +44 (0) 1993 708811
Fax +44 (0) 1993 708787
Email sales@del-uk.com
www.del-uk.com